



PREPARATION AND APPLICATION PROCEDURE

ACRYLIC COATINGS (EIFS)

PREPARATION	FINISH	SEALANT
<p>Procedure:</p> <ul style="list-style-type: none">- Thoroughly rinse the surface with a pressure washer.- Apply TexNov Surface Preparer.- Vigorously brush the surface and allow 15 minutes for it to act.- Rinse the surface thoroughly with a pressure washer.- Let the surface dry over a period of 48 hours of good weather before applying the finish coat.	<p>After preparing the surface:</p> <p>Procedure:</p> <ul style="list-style-type: none">- Apply two coats of TexNov Acrylic Coating. Use a brush or roller with 10 mm bristles (24 hours between each coat).- Let the surface dry for 24 hours.	<p>After preparing the surface and applying the coating:</p> <p>Procedure:</p> <ul style="list-style-type: none">- Apply 2 coats of TexNov WRS-40 Sealant (waterproof sealant) to waterproof the surface. Use a brush or roller with 10 mm bristles or a sprayer (24 hours between each coat). (Optional)- Let the surface dry for 24 hours.

Maintenance: Clean the surface with **TexNov Surface Preparer** (3 water / 1 Preparer). Let dry and add a coat of **WRS-40 Sealant** every 5 years or as needed. This should enable you to keep your surface in good condition.

